
Typical chemical and physical Properties **D'FOAM BIL 5048** is a water-dispersible defoamer for paper coating systems.
It also performs as a de-aerator by bursting bubbles of entrained air in the coating media.

A Blend of vegetable oils, petroleum wax and glycols

PROPERTIES:

Appearance	Milky paste
Active content	48 ± 2 %
Solubility	Dispersible in water

Applications and typical treat level recommended

Paper Coating 1% to 2% of weight of coating -media

It is recommended to use a 20% dispersion of **D'FOAM BIL 5048** for easy handling. A homogeneous dispersion can be prepared by gradually adding water, giving gentle but continued stirring.

Benefits

D'FOAM BIL 5048 is a 50% active product and performs tremendously in controlling foam generation and in removal of entrained air in coating systems.

It efficiently performs de-aeration function by bursting bubbles of entrained air in the coating media.

Disclaimer:

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.