

Typical chemical and physical D'FOAM ACC 62

Liquid is an effective antifoam suited for Oil well cement Slurries.

Properties

It is particularly designed to eject entrained air from Organic admixtures. It is also used in making Polyvinyl alcohol based clear adhesives as it does not Impart haze to the final product.

Combination of Polyalkylene Glycols

PROPERTIES:

Appearance	Pa;e Yellow viscous clear liquid
Active content	100 %
Dispersibility/ Solubility	Dispersible in water
pH	7 ± 1

Applications and typical treat level recommended

D'FOAM ACC 62 Liquid can be easily added / blended into admixture formulations. Recommended level of addition is approx. 0.08 % to 0.14% of total weight to remove and contro the entrained air in the given system.

Benefits

D'FOAM ACC 62 Liquid reduces entrained air without changing slurry properties

The minimum dosage required will depend upon the organics which are present. **D'EFOAM ACC 62 Liquid** will eliminate entrained air which causes problem in pumping, Trowelling and complete cavitt filling. It will also prevent excessive shrinkage, Porosity and weakness of the set cement.

Disclaimer:

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.
