

---

**Typical chemical and physical Properties**

**D'FOAM ACC PBT** is a defoamer in free- flowing powder form for concrete **additives**. It is useful in formulations which requires the use of Organic Admixtures but where entrained air must be avoided. DEFOAM PWD PBT is also suitable emulsion paints and adhesives .

PROPERTIES:

Appearance	Off white powder
Ionic Nature	Non - Ionic
Active content	65 %
Dispersibility/Solubility	Dispersible in water
PH	8.5 ± 1.0

---

**Applications and typical treat level recommended**

Dosage Recommended 0.1 % - 0.4 %

**D'FOAM ACC PBT** can be easily added/blended into admixtures formulations. Recommended level of addition is approx 0.1% to 0.4% of total weight to remove and control the entrained air in the given system.

---

**Benefits**

**D'FOAM ACC PBT** reduces entrained air without changing slurry properties. Recommended dosage level is 0.1% to 0.4% by weight of water, eliminates entrained air in most systems.

The minimum dosage required will depend upon the organics which are present. **D'FOAM ACC PBT** will eliminate entrained air, which causes problem in pumping, trowling and complete cavity filling. It will also prevent excessive shrinkage, porosity and weakness of the set cement.

**Disclaimer:**

*All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*