
General Purpose

Typical chemical and physical Properties

D'FOAM APS 20 is a silicone-based defoamer catering to multiple **applications** across wide spectrum of industries such as industrial cleaning, Paints & Coatings , waste water treatment etc.

A Blend of polydimethyl siloxane, silica, polyether silicones and surfactants

PROPERTIES:

Appearance	Milky free- flowing liquid
Solid content	Min. 20 %
Dilution Water	
pH	7.5 ± 1.0
Specific Gravity	approx. 1.00
Ionicity	Non-Ionic

Applications and typical treat level recommended

Dosage 0.3% to 0.7%

It is recommended to use **D'FOAM APS 20** in its natural state. It may also be distributed with a water dilution system and / or with a special metering system for automatic dosing, which means product will be automatically added only when needed.

Benefits

D'FOAM APS 20 performs tremendously in controlling foam generation in general chemical processing applications such as industrial cleaning, waste water treatment, Paints & coatings etc.

It is very effective even at low concentrations and facilitates smoother pump operation, transport.

D'FOAM APS 20 leaves no residues in the pipes or valves of the equipment used.

Disclaimer:

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.