

General Purpose

Typical chemical and physical properties

D'FOAM BIL 0253 is a revolutionary antifoam formulation for Brown stock washing. It is silicone-based and imparts superior "foam knock-down" effect at low dosage level. It is used in multiple applications such as Industrial cleaning, waste water – treatment, Gas Sweetening and Gas drying.

A Proprietary blend of polydimethylsiloxane, silicone Glycol and other surface active components.

PROPERTIES:

Appearance	Milky free-flowing emulsion
Solid content	> 25%
Specific gravity at 25 °C	approx. 1.00 g/cm ³

Applications and typical treat level recommended

D'FOAM BIL 0253 may be pre-diluted by adding water into it in a pre-mixing vessel.
Caution: Do not add D'FOAM BIL 0253 into water.

Apply the product in its natural state by aspersion or by dosing pump and adjust the initial dosage according to the requirements.

Benefits

D'FOAM BIL 0253 is a 25% product and shows excellent performance in the control of foams by significantly reducing the entrained air content.

It is very effective even at low concentrations and facilitates smoother pump operation, transport.

D'FOAM BIL 0253 leaves no residues in the pipes or valves of the equipment used.

Disclaimer

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.
