

---

### Typical chemical and physical properties

**D'FOAM BIL 1605** is a revolutionary antifoam formulation dedicated for PULP MILL applications. It is silicone-based and imparts superior "foam knock-down" effect at low dosage levels.

**A Proprietary blend of polydimethylsiloxane and other surface active components.**

#### PROPERTIES:

Appearance	Milky free-flowing emulsion
Solid content	10.5 ± 1%
Specific gravity at 25 °C	approx. 1.00 g/cm <sup>3</sup>

---

### Applications and typical treat level recommended

Pulping 300 -500 grams / tonne of Paper

**D'FOAM BIL 1605** may be pre-diluted by adding water into it in a pre-mixing vessel.  
Caution: Do not add TIPAP 1605 into water.

Apply the product in its natural state by aspersion or by dosing pump and adjust the initial dosage according to the requirements.

---

### Benefits

**D'FOAM BIL 1605** shows excellent performance in the control of foams by significantly reducing the entrained air content.

It is very effective even at low concentrations and facilitates smoother pump operation, transport.

**D'FOAM BIL 1605** leaves no residues in the pipes or valves of the equipment used.

#### Disclaimer

*All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

---